

Stair Nosing - Standard



OPTIONS

Standard Colour:
Yellow RAL 1003

Colours to order:
Any RAL / BS colour*

Dimensions:
Manufactured on a nominally 4mm thick
GRP profile giving a finished thickness of
typically 5-6mm. Integral downstand.

Stocked profiles:
Length: 3200 mm
Depth x downstand:
70 mm x 30 mm
55 mm x 55 mm (Equality Act
Compliant)

Additional Options:
Chamfered & resin finished edges
Pre-drilled fixing points
Choice of colour
Choice of grit size*
Cut to exact sizes prior to delivery
Full range of fasteners & adhesives for all
on-site scenarios

SPECIFICATION

Profile & resin coatings:
High quality isophthalic polyesters

Grit:
Refined aluminium oxide

Hardness:
9.5 moh / 2200 knoop diamond

Suitable traffic:
Foot

Can be fixed to:
Chequerplate, concrete, metal, wood,
ceramics, open mesh grating

Fixing methods:
Sealant/adhesive in combination with
countersunk/panhead screws or self-
drilling screws

* Minimum order quantities apply. Please
contact us for further information.

BENEFITS

- > highly effective anti-slip safety surface
- > long lasting & durable
- > suitable for all environments, exterior or interior
- > refined, extra-hard aluminium oxide granules give superior performance & wear characteristics (compared to common quartz grit finishes), industrial (grade 16, medium/coarse)
- > far outlasts anti slip tapes, floor paints & coatings
- > little or no maintenance requirement
- > light weight profiles add insignificant load to existing structures
- > rapid & easy installation - choice of fasteners/adhesives to suit any existing surface
- > resistant to a wide range of chemicals (full details available)
- > full range of RAL & BS colours available to order
- > Equality Act compliant products available
- > conforms to UK Building Regulations
- > easily cleanable
- > rapid delivery: typically 3-5 days for stocked items & 10 weeks for bespoke products*
- > free cutting service*

APPLICATIONS

Typical applications:

- staircases
- steps

DESCRIPTION

A nominally 4mm thick, tough GRP profiled cover, coated in a combination of premium quality aluminium oxide & resin components gives the Stair Nosing product a highly effective and durable Anti-slip surface that will withstand the rigours of most industrial & commercial environments. Designed specifically to reduce the risk of slipping on step edges, they are the preferred choice over tapes and paints, offering an almost permanent solution to slip hazards. The products can be laid and fixed using a combination of adhesive/sealant and fasteners to effectively fix, bond and seal the edges, preventing any ingress of moisture.

In conformance with parts M1/M2 of the Building Regulations and Equality Act legislation (formerly Disability Discrimination Act) the nosings are made apparent by means of a permanently contrasting material on both the tread and riser. Also the surfaces are firm, durable and slip-resistant.

The product may also be chamfered back and leading edges to further reduce the possibility of a trip hazard.

Designed to be fixed to all substrate types with a choice of fixing methods available at despatch.

To accommodate all requirements, stocks of standard product types are always available, complemented by rapid, bespoke made solutions direct from our UK manufacturing facilities.